

[illegible]

3

Sy
--
MT
MT
MT

[illegible]

MT
MT
MT
MT
MT
MT
MT

MT
MT
MT
MT
MT
MT
MT

MM	MM	TTTTTTTTTT	HH	HH	GGGGGGGG	EEEEEEEEEE	XX	XX	PPPPPPPP	
MM	MM	TTTTTTTTTT	HH	HH	GGGGGGGG	EEEEEEEEEE	XX	XX	PPPPPPPP	
MMM	MMM	TT	HH	HH	GG	EE	XX	XX	PP	PP
MMM	MMM	TT	HH	HH	GG	EE	XX	XX	PP	PP
MM	MM	TT	HH	HH	GG	EE	XX	XX	PP	PP
MM	MM	TT	HH	HH	GG	EE	XX	XX	PP	PP
MM	MM	TT	HHHHHHHHHH	HH	GG	EEEEEEEE		XX	PPPPPPPP	
MM	MM	TT	HHHHHHHHHH	HH	GG	EEEEEEEE		XX	PPPPPPPP	
MM	MM	TT	HH	HH	GG	GGGGGG	XX	XX	PP	
MM	MM	TT	HH	HH	GG	GGGGGG	XX	XX	PP	
MM	MM	TT	HH	HH	GG	GG	XX	XX	PP	
MM	MM	TT	HH	HH	GG	GG	XX	XX	PP	
MM	MM	TT	HH	HH	GG	GG	XX	XX	PP	
MM	MM	TT	HH	HH	GG	GG	XX	XX	PP	
MM	MM	TT	HH	HH	GGGGGG	EEEEEEEEEE	XX	XX	PP	
MM	MM	TT	HH	HH	GGGGGG	EEEEEEEEEE	XX	XX	PP	

```
LL      IIIIII    SSSSSSSS  
LL      IIIII I   SSSSSSSS  
LL          II     SS       SS  
LL        II      SS       SS  
LL        II      SS       SS  
LL        II      SSSSSS  
LL        II      SSSSSS  
LL        II              SS  
LL        II             SS  
LL        II            SS  
LL        II           SS  
LLLLLLLLLLLLL  IIIII I  SSSSSSSS  
LLLLLLLLLLLLL  IIIII I  SSSSSSSS
```

(2)	50
(3)	63
(4)	233
(5)	287

HISTORY : Detailed Current Edit History
DECLARATIONS : Declarative Part of Module
MTH\$GEXP - Standard G Floating EXP
MTH\$GEXP_R6 - Special GEXP routine


```
0000 1 .TITLE MTH$GEXP ; G Floating Exponential Function
0000 2 ; (DEXP)
0000 3 .IDENT /1-006/ ; File: MTHGEXP.MAR Edit:RNH1006
0000 4 :
0000 5 :*****
0000 6 :
0000 7 :* COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 8 :* DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 9 :* ALL RIGHTS RESERVED.
0000 10 :
0000 11 :* THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 12 :* ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 13 :* INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 14 :* COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 15 :* OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 16 :* TRANSFERRED.
0000 17 :
0000 18 :* THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 19 :* AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 20 :* CORPORATION.
0000 21 :
0000 22 :* DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 23 :* SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 24 :
0000 25 :
0000 26 :*****
0000 27 :
0000 28 :
0000 29 : FACILITY: MATH LIBRARY
0000 30 : ++
0000 31 : ABSTRACT:
0000 32 :
0000 33 : MTH$GEXP is a function which returns the G floating point
0000 34 : exponential of its G floating point argument.
0000 35 : The call is standard call-by-reference.
0000 36 :
0000 37 : --
0000 38 :
0000 39 : VERSION: 1
0000 40 :
0000 41 : HISTORY:
0000 42 : AUTHOR:
0000 43 : Steven B. Lionel, 15-Jan-79: Version 1
0000 44 :
0000 45 : MODIFIED BY:
0000 46 :
0000 47 :
0000 48 :
```

MTH\$GEXP
1-006

J 11
; G Floating Exponential Function 16-SEP-1984 01:27:00 VAX/VMS Macro V04-00
HISTORY ; Detailed Current Edit History 6-SEP-1984 11:23:37 [MTHRTL.SRC]MTHGEXP.MAR;1

Page 2
(2)

```
0000 50      .SBTTL HISTORY ; Detailed Current Edit History
0000 51
0000 52 : Edit History for Version 1 of MTH$GEXP
0000 53
0000 54 : 1-001 - Adapted from MTH$GEXP version 1-008. SBL 15-Jan-79
0000 55 : 1-002 - Corrected a typo in the title. JBS 30-JUL-1979
0000 56 : 1-003 - Use only through R6. SBL 21-Sept-1979
0000 57 : 1-004 - Added large argument logic to avoid lose of significance in
0000 58 : EMOD for arguments greater than 2**7. RNH 24-JUN-81
0000 59 : 1-005 - Changed W^ to G^ on calls to MTH$$SIGNAL and MTH$$JACKET_TST
0000 60 : RNH 09-Sept-1981
0000 61 : 1-006 - Eliminated symbolic short literals
```



```
0000 63 .SBTTL DECLARATIONS ; Declarative Part of Module
0000 64
0000 65 :
0000 66 : INCLUDE FILES: MTHJACKET.MAR
0000 67 :
0000 68 : EXTERNAL SYMBOLS:
0000 69 :
0000 70 .DSABL GBL ; Declare all EXTRNs explicitly
0000 71 .EXTRN MTH$$SIGNAL ; SIGNAL SEVERE error
0000 72 .EXTRN MTH$$JACKET_TST ; Test to see if called with CALL or
0000 73 ; JSB
0000 74 .EXTRN MTH$K_FLOUNDMAT ; Underflow error code
0000 75 .EXTRN MTH$K_FLOOVEMAT ; Overflow error code
0000 76
0000 77 ; EQUATED SYMBOLS:
0000 78
0000 79 ACMASK = ^M<IV, R2, R3, R4, R5, R6> ; .ENTRY mask + int ovf enable
0000 80 X_16LOG2E = ^0013540 ; Extension for operand in EMOVG
0000 81 :
0000 82 : MACROS:
0000 83 $SFDEF ; define SF$ (stack frame) symbols
0000 84 :
0000 85 : PSECT DECLARATIONS:
0000 86
00000000 87 .PSECT _MTH$CODE PIC,SHR, LONG, EXE, NOWRT
0000 88 ; program section for math routines
0000 89 :
0000 90 : OWN STORAGE: none
0000 91 :
0000 92 : CONSTANTS:
0000 93 :
0000 94 :
0000 95 : Table to be used for scaling. These constants here have been
0000 96 : verified by M. Payne using her program ROOT16 on PDP-10.
0000 97 :
0000 98 TABHI: .WORD ^0040020,0 ; 2**(0/16) = 1.0
0000 99 .WORD 0,0
0000 100 .WORD ^0040020, ^0132530 ; 2**(1/16)
0000 101 .WORD ^0066371, ^0104417
0000 102 .WORD ^0040021, ^0071270 ; 2**(2/16)
0000 103 .WORD ^0036175, ^0050572
0000 104 .WORD ^0040022, ^0034172 ; 2**(3/16)
0000 105 .WORD ^0067165, ^0061070
0000 106 .WORD ^0040023, ^0003376 ; 2**(4/16)
0000 107 .WORD ^0005061, ^0133425
0000 108 .WORD ^0040023, ^0157246 ; 2**(5/16)
0000 109 .WORD ^0046022, ^0032042
0000 110 .WORD ^0040024, ^0137732 ; 2**(6/16)
0000 111 .WORD ^0152466, ^0025047
0000 112 .WORD ^0040025, ^0125407 ; 2**(7/16)
0000 113 .WORD ^0156510, ^0052051
0000 114 .WORD ^0040026, ^0120236 ; 2**(8/16)
0000 115 .WORD ^0063177, ^0035714
0000 116 .WORD ^0040027, ^0120424 ; 2**(9/16)
0000 117 .WORD ^0071753, ^0000606
0000 118 .WORD ^0040030, ^0126345 ; 2**(10/16)
0000 119 .WORD ^0041052, ^0120333
```

```
C491 4019 0058 120 .WORD ^0040031,^0142221 ; 2**(11/16)
F090 82A3 005C 121 .WORD ^0101243,^0170220
E89F 401A 0060 122 .WORD ^0040032,^0164237 ; 2**(12/16)
D3AD 995A 0064 123 .WORD ^0114532,^0151655
199B 401C 0068 124 .WORD ^0040034,^0014633 ; 2**(13/16)
529C DD85 006C 125 .WORD ^0156605,^0051234
5818 401D 0070 126 .WORD ^0040035,^0054030 ; 2**(14/16)
A487 DCFB 0074 127 .WORD ^0156373,^0122207
A4AF 401E 0078 128 .WORD ^0040036,^0122257 ; 2**(15/16)
90D9 A2A4 007C 129 .WORD ^0121244,^0110331
0080 130
0080 131
0080 132
0080 133
0080 134
0080 135
0080 136
0080 137
0080 138
0080 139
```

```
+++
\\ NOTE!!!: The decimal equivalents in TABLO are taken
directly from MTHSGEXP. They do not correspond to the
actual value of the G floating equivalent. When an entry
in TABHI and its corresponding entry in TABLO are added, they
should equal the correct fractional power of 2 to 74 bits. \\
--
```

```
0000 0000 0080 140 TABLO: .WORD 0,0 ; DECIMAL: 0.D0
0000 0000 0084 141 .WORD 0,0
A62E 3CB8 0088 142 .WORD ^0036270,^0123056 ; DECIMAL: 0.2252169616881804D-17
0000 0000 008C 143 .WORD 0,0
9BF0 3CCF 0090 144 .WORD ^0036317,^0115760 ; DECIMAL:-0.2712242510500122D-17
0000 0000 0094 145 .WORD 0,0
B07F 3CB9 0098 146 .WORD ^0036271,^0130177 ; DECIMAL: 0.5861402647731367D-17
0000 0000 009C 147 .WORD 0,0
F46B 3CA6 00A0 148 .WORD ^0036246,^0172153 ; DECIMAL: 0.1206457647223494D-16
0000 0000 00A4 149 .WORD 0,0
DA09 3CAA 00A8 150 .WORD ^0036252,^0155011 ; DECIMAL:-0.8930877995013540D-17
0000 0000 00AC 151 .WORD 0,0
4398 3C9D 00B0 152 .WORD ^0036235,^0041630 ; DECIMAL:-0.2373071989573779D-17
0000 0000 00B4 153 .WORD 0,0
324C 3CB6 00B8 154 .WORD ^0036266,^0031114 ; DECIMAL:-0.6257240830881880D-17
0000 0000 00BC 155 .WORD 0,0
1166 3CC6 00C0 156 .WORD ^0036306,^0010546 ; DECIMAL:-0.1340620676392399D-16
0000 0000 00C4 157 .WORD 0,0
FAA2 3CCE 00C8 158 .WORD ^0036316,^0175242 ; DECIMAL:-0.7084371812598154D-17
0000 0000 00CC 159 .WORD 0,0
E9F1 3CB6 00D0 160 .WORD ^0036266,^0164761 ; DECIMAL:-0.3768379065187162D-17
0000 0000 00D4 161 .WORD 0,0
7C47 3C9C 00D8 162 .WORD ^0036234,^0076107 ; DECIMAL:-0.3048384309613603D-17
0000 0000 00DC 163 .WORD 0,0
A1CD 3CB7 00E0 164 .WORD ^0036267,^0120715 ; DECIMAL:-0.1276624235300040D-17
0000 0000 00E4 165 .WORD 0,0
1066 3CA1 00E8 166 .WORD ^0036241,^0010146 ; DECIMAL: 0.1845830375854930D-17
0000 0000 00EC 167 .WORD 0,0
ED03 3CA2 00F0 168 .WORD ^0036242,^0166403 ; DECIMAL: 0.5075495866202897D-17
0000 0000 00F4 169 .WORD 0,0
B1EE 3CC0 00F8 170 .WORD ^0036300,^0130756 ; DECIMAL: 0.4822843060675619D-17
0000 0000 00FC 171 .WORD 0,0
0100 172
0100 173
0100 174
0100 175
```

```
: Constants used in evaluation of polynomials - small arguments
```

```
0259 3F1A 0100 176 GXPTB1: .WORD ^0037432,^0001131
```



```
9943 0B6E 0104 177 .WORD ^0005556,^0114503 ; DECIMAL: 0.2480427857745020D-04
0270 3F4A 0108 178 .WORD ^0037512,^0001160
32C6 29E6 010C 179 .WORD ^0024746,^0031306 ; DECIMAL: 0.1984369200268758D-03
C16C 3F76 0110 180 .WORD ^0037566,^0140554
1C67 143A 0114 181 .WORD ^0012072,^0016147 ; DECIMAL: 0.1388888879690042D-02
1111 3FA1 0118 182 .WORD ^0037641,^0010421
DE80 0EA0 011C 183 .WORD ^0007240,^0157200 ; DECIMAL: 0.8333333262370290D-02
5555 3FC5 0120 184 .WORD ^0037705,^0052525
5C8F 5555 0124 185 .WORD ^0052525,^0056217 ; DECIMAL: 0.4166666666667950D-01
5555 3FE5 0128 186 .WORD ^0037745,^0052525
602C 5555 012C 187 .WORD ^0052525,^0060054 ; DECIMAL: 0.1666666666667437D-00
0000 4000 0130 188 .WORD ^0040000,0
0000 0000 0134 189 .WORD 0,0 ; DECIMAL: 0.5000000000000000D-00
FFFF 400F 0138 190 .WORD ^0040017,^0177777
FFFF FFFF 013C 191 .WORD ^0177777,^0177777 ; DECIMAL: 0.1000000000000000D+01
0000 4010 0140 192 .WORD ^0040020,0
0000 0000 0144 193 .WORD 0,0 ; DECIMAL: 0.1000000000000000D+01
00000009 0148 194 GXPLN1=<.-GXPTB1>/8 ; no. of entries in table
0148 195
0148 196 ;
0148 197 ; Constants used in evaluation of polynomial - regular args
0148 198 ;
0148 199
0148 200
2C4D 3CD6 0148 201 GXPTAB: .WORD ^0036326,^0026115
F542 E47E 014C 202 .WORD ^0162176,^0172502 ; DECIMAL: 0.3077130709430240D-15
FD3A 3D4F 0150 203 .WORD ^0036517,^0176472
FOE2 B8D3 0154 204 .WORD ^0134323,^0170342 ; DECIMAL: 0.5682419384166091D-13
3091 3DC4 0158 205 .WORD ^0036704,^0030221
35C8 2F02 015C 206 .WORD ^0027402,^0032710 ; DECIMAL: 0.9181219559808114D-11
D87F 3E35 0160 207 .WORD ^0037065,^0154177
F9D7 E6D1 0164 208 .WORD ^0163321,^0174727 ; DECIMAL: 0.1271587192556359D-08
B2AB 3EA3 0168 209 .WORD ^0037243,^0131253
4F35 6FBA 016C 210 .WORD ^0067672,^0047465 ; DECIMAL: 0.1467610032291993D-06
6B08 3F0C 0170 211 .WORD ^0037414,^0065410
A25A D704 0174 212 .WORD ^0153404,^0121132 ; DECIMAL: 0.1355080777949815D-04
BFBD 3F6E 0178 213 .WORD ^0037556,^0137675
C58F FF82 017C 214 .WORD ^0177602,^0142617 ; DECIMAL: 0.9383847928089872D-03
2E42 3FC6 0180 215 .WORD ^0037706,^0027102
39EF FEFA 0184 216 .WORD ^0177372,^0034757 ; DECIMAL: 0.4332169878499658D-01
0000 0000 0188 217 .WORD 0,0
0000 0000 018C 218 .WORD 0,0 ; DECIMAL: 0
00000009 0190 219 GXPLN=<.-GXPTAB>/8 ; no. of entries in table
0190 220
0190 221
0190 222 G_16LOG2_E: ; LOG2(E) * 16
1547 4057 0190 223 .WORD ^0040127,^0012507
82FE 652B 0194 224 .WORD ^0062453,^0101376
0198 225
0198 226 G_LN2_OV_16_HI:
0000FEFA 2E423FC6 0198 227 .QUAD ^X0000FEFA2E423FC6 ; Hi 39 bits of ln2/16
01A0 228
01A0 229 G_LN2_OV_16_LO:
3B3ABC9E F79A3D5C 01A0 230 .QUAD ^X3B3ABC9EF79A3D5C ; Low bits of ln2/16
01A8 231
```



```
01A8 233      .SBTTL MTH$GEXP - Standard G Floating EXP
01A8 234
01A8 235
01A8 236      ++
01A8 237      FUNCTIONAL DESCRIPTION:
01A8 238
01A8 239      EXP - G floating point function
01A8 240
01A8 241      Uses a Chebyshev approximation, with overhang on last step.
01A8 242
01A8 243
01A8 244      CALLING SEQUENCE:
01A8 245
01A8 246      Exponential.wg.v = MTH$GEXP(x.rg.r)
01A8 247
01A8 248      INPUT PARAMETERS:
01A8 249
00000004 01A8 250      LONG = 4                      ; define longword multiplier
00000004 01A8 251      x = 1 * LONG                      ; Contents of x is the argument
01A8 252
01A8 253      IMPLICIT INPUTS:      none
01A8 254
01A8 255      OUTPUT PARAMETERS:
01A8 256
01A8 257      VALUE: G floating exponential of the argument
01A8 258
01A8 259      IMPLICIT OUTPUTS:      none
01A8 260
01A8 261      SIDE EFFECTS:
01A8 262
01A8 263      Signals: MTH$_FLOOVEMAT if X > 709 with reserved operand in R0/R1 (copied
01A8 264      to the signal mechanism vector CHF$MCH_R0/R1 by LIB$SIGNAL). Associated
01A8 265      message is: "FLOATING OVERFLOW IN MATH LIBRARY". Result is reserved operand
01A8 266      -0.0 unless a user supplied (or any) error handler changes CHF$MCH_R0/R1.
01A8 267      MTH$_FLOUNDMAT if X <= -709 and caller has hardware enable set. The
01A8 268      result is set to +0.0. Associated message is: "FLOATING UNDERFLOW IN MATH
01A8 269      LIBRARY"
01A8 270
01A8 271      NOTE: This procedure disables floating point underflow, enable integer
01A8 272      overflow, causes no floating overflow or other arithmetic traps, and
01A8 273      preserves enables across the call.
01A8 274
01A8 275      --
01A8 276
01A8 277
407C 01A8 278      .ENTRY MTH$GEXP, ACMASK                      ; standard call-by-reference entry
01AA 279      MTH$FLAG_JACKET                      ; disable DV (and FU), enable IV
01AA 280      ; flag that this is a jacket procedure
01AA
6D 00000000'GF 9E 01AA      MOVAB G^MTH$$JACKET_HND, (FP)      ; set handler address to jacket
01B1      ; handler
01B1
01B1 281      ; in case of an error in special JSB
01B1 282      ; routine
50 04 BC 50FD 01B1 283      MOVG @x(AP), R0      ; R0/R1 = user's arg
01 10 01B6 284      BSBB MTH$GEXP_R6      ; R0/R1 = special EXP(R0/R1)
```

MTH\$GEXP
1-006

: G Floating Exponential Function B 12
MTH\$GEXP - Standard G Floating EXP

16-SEP-1984 01:27:00 VAX/VMS Macro V04-00
6-SEP-1984 11:23:37 [MTHRTL.SRC]MTHGEXP.MAR;1

Page 7
(4)

04 01B8 285 RET

; return - result in R0/R1


```

01B9 287      .SBTTL  MTH$GEXP_R6 - Special GEXP routine
01B9 288
01B9 289      ; Special GEXP - used by the standard, and direct interfaces.
01B9 290
01B9 291      CALLING SEQUENCE:
01B9 292      ; save anything needed in R0:R6
01B9 293      ; MOVG      R0          ; input in R0
01B9 294      ; JSB      MTH$GEXP_R6
01B9 295      ; return with result in R0/R1
01B9 296
01B9 297      ; Note: This routine is written to avoid causing any integer overflows,
01B9 298      ; floating overflows, or floating underflows or divide by 0 conditions,
01B9 299      ; whether enabled or not.
01B9 300
01B9 301      REGISTERS USED:
01B9 302      ; R0/R1 - floating argument, then result
01B9 303      ; R2/R3 - temp
01B9 304      ; R5 - integer scratch
01B9 305      ; R6 - integer part of X * LG2(E) * 16    (16I+J)
01B9 306
01B9 307
01B9 308      MTH$GEXP_R6::          ; special GEXP routine
01B9 309      MTH$GEXP_R7::          ; Release 1 name
01B9 310      ;+
01B9 311      ; The preliminary test for overflow works as follows: First, the sign bit is
01B9 312      ; cleared leaving the first word of the !X!. Then, 1024-4 (bias-4) is sub-
01B9 313      ; tracted, leaving an exponent biased by 4 in bits 14:4 and the first four
01B9 314      ; fraction bits in 3:0. This rebased value is compared against 230 (decimal).
01B9 315      ; The comparison can have 3 outcomes. If the rebased value is now negative,
01B9 316      ; this means that the true exponent is < -4 - this is a BLSSU test. If the
01B9 317      ; rebased value is positive, but greater than 230 (decimal), then the !X! is
01B9 318      ; greater than or equal to 736, which is guaranteed overflow or underflow,
01B9 319      ; depending on the sign of X - this is a BLSS test. Otherwise, X is somewhere
01B9 320      ; in the range for the standard evaluation, and flow continues.
01B9 321      ; -
01B9 322      ; -
52  50  8000 8F  AB 01B9 323      BICW3    #^X8000, R0, R2          ; Preliminary test for over/underflow
01BF 324      ; R2 = exponent bits only
53  52  3FC0 8F  A3 01BF 325      SUBW3    #^X3FC0, R2, R3          ; R3 = 4 + unbiased exponent
53  53  00E6 8F  B1 01BF 326      CMPW     #^XE6, R3          ; unsigned compare of !X! with 732
      6B  1F 01C5 327      CMPW     #^XE6, R3          ; to more tests if LSSU
      01CA 328      BLSSU    SMTST          ; else, -4 < unbiased exp < 11
      01CC 329      ; no exceptions in EMODG or APPROX
      01CC 330
      4080 8F  52  B1 01CC 331      CMPW     R2, #^X4080          ; Check for loss of significance in
      01D1 332      ; EMOD ( !X! >= 2**7
      28  19 01D1 333      BLSS     EVAL          ; No loss of significance
      01D3 334
      01D3 335      ;
      01D3 336      ; !X! >= 2**4. EMOD will lose significance so the interger and fractional
      01D3 337      ; parts of X*16/ln2 must be obtained in seperate steps.
      01D3 338      ;
52  50  B9  AF  45FD 01D3 339      MULG3    G 16LOG2_E, R0, R2          ; Get integer part of X*16/ln2 in
      56  52  4AFD 01D9 340      CVTGL     R2, R6          ; R6 (=I+J) as a longword and in
      52  56  4EFD 01DD 341      CVTGL     R6, R2          ; R2/R3 in G format
54  52  B3  AF  45FD 01E1 342      MULG3    G LN2_OV_16_HI, R2, R4          ; Get fraction part of X*16/ln2 =
      50  54  42FD 01E7 343      SUBG2     R4, R0          ; 16/ln2*[ X - (I+J)*ln2/16 ]

```



```
52 B1 AF 44FD 01EB 344 MULG2 G_LN2_OV_16_LO, R2 ; in R0/R1.
50 50 52 42FD 01F0 345 SUBG2 R2, R0 ;
50 98 AF 44FD 01F4 346 MULG2 G_16LOG2_E, R0 ;
OA 11 01F9 347 BRB APPROX ;
01FB 348
50 56 50 1760 8F 91 AF 54FD 01FB 349 EVAL: EMODG G_16LOG2_E, #X_16LOG2E, R0, R6, R0 ;
0205 350 ; get X*16*LG2(E) with
0205 351 ; integer part in R6 (=16I+J)
0205 352 ; fraction in R0/R1
0205 353
FF3C CF 08 50 55FD 0205 354 APPROX: POLYG R0, #GXPLN-1, GXPTAB ; use Chebyshev series
020C 355 ; with last coefficient 0
020C 356 ; so that last ADDG has overhang
020C 357
55 56 FFFFFFFF 8F CB 020C 358 BICL3 #-16, R6, R5 ; R5 = J
50 FDE6 CF45 44FD 0214 359 MULG2 TABHI[R5], R0 ; else MUL by 2**(J/16)
50 FE5F CF45 40FD 021B 360 ADDG2 TABLO[R5], R0 ; add in LO of 2**(J/16)
50 FDD8 CF45 40FD 0222 361 ADDG2 TABHI[R5], R0 ; and then HI of 2**(J/16)
0229 362
56 0F CA 0229 363 BICL #15, R6 ; R6 = I
08 13 022C 364 BEQL 20$ ; if I=0, then done
50 56 C0 022E 365 ADDL2 R6, R0 ; Add I to exponent.
0F 50 B1 0231 366 CMPW R0, #^XF ; MUL by 2**I by exponent addition
40 15 0234 367 BLEQ EXCEPT ; test for over/underflow
05 0236 368 RSB ; see what exception is if neg or = 0
0237 369 20$: ; otherwise return result in R0
0237 370
3C80 8F 14 19 0237 371 SMTST: ;
52 B1 0237 372 BLSS 20$ ; exception if exp+4 > 14
08 19 0239 373 CMPW R2, #^X3C80 ; eliminate underflow from APPROX1
023E 374 BLSS 10$ ; bypass if E**ARG = 1
0240 375
0240 376 ;+
0240 377 ; Use Chebyshev series for small arg
0240 378 ; -
0240 379
FEB9 CF 08 50 55FD 0240 380 POLYG R0, #GXPLN1-1, GXPTB1 ; Use Chebyshev series
0247 381 ; last term is 1; this will
0247 382 ; give desired overhang.
05 0247 383 RSB ; answer is OK, return
0248 384
50 08 50FD 0248 385 10$: MOVG S^#1, R0 ; E**X is 1, store it
05 024C 386 RSB ; and return
024D 387
024D 388
024D 389 ;
024D 390 ; Handlers for software detected over/underflow conditions follow
024D 391 ;
50 53FD 024D 392 20$: TSTG R0 ; if big ARG > 0 goto OVERFLOW
28 18 0250 393 BGEQ OVER
0252 394 ;
0252 395 ; Underflow; if user has FU set, signal error. Always return 0.0
0252 396 ;
0252 397 UNDER:
00000000'GF 52 DC 0252 398 MOVPSL R2 ; R2 = user's or jacket routine's PSL
04 00 FB 0254 399 CALLS #0, G^MTH$$JACKET_TST ; R0 = TRUE if JSB from jacket routine
05 E9 025B 400 BLBC R0, 10$ ; branch if user did JSB
```

```

52 04 AD 3C 025E 401      MOVZWL  SF$W_SAVE_PSW(FP), R2      ; get user PSL saved by CALL
50      7C 0262 402 10$: CLRQ    R0                        ; R0 = result. LIB$SIGNAL will save in
                                403                        ; CHF$MCH_R0/R1 so any handler can fixup
0D 52 06 E1 0264 404      BBC     #6, R2, 20$              ; has user enabled floating underflow?
                                405      PUSHL  (SP)          ; yes, return PC from special routine
7E 00'8F 9A 026A 406      MOVZBL  #MTH$K_FLOUNDMAT, -(SP)    ; trap code for hardware floating underflow
                                407                        ; convert to MTH$FLOUNDMAT (32-bit VAX-11
                                408                        ; exception code)
00000000'GF 02 FB 026E 409      CALLS  #2, G^MTH$$$SIGNAL    ; signal (condition, PC)
                                05 0275 410 20$: RSB          ; return
                                411
                                412 EXCEPT:
56      D5 0276 413      TSTL     R6                        ; test sign of I; if I < 0
D8      19 0278 414      BLSS    UNDER                    ; go to underflow handler
                                415      ;
                                416      ; Signal floating overflow, return reserved operand, -0.0
                                417      ;
                                418 OVER:
7E 00'8F 6E DD 027A 419      PUSHL  (SP)                    ; else process for overflow
50 01 0F 79 027A 420      MOVZBL  #MTH$K_FLOOVEMAT, -(SP)    ; return PC from special routine
                                421      ASHQ     #15, #T, R0  ; hardware floating overflow
                                422                        ; R0/R1 = result = reserved operand
                                423                        ; -0.0. R0/0 will be copied to
                                424                        ; signal mechanism vector (CHF$MCH_R0/R1)
                                425                        ; so can be fixed up by any error
                                426      CALLS  #2, G^MTH$$$SIGNAL ; handler
00000000'GF 02 FB 0284 426      RSB          ; signal (condition, PC)
                                05 028B 427      ; return - R0 restored from CHF$MCH_R0/R1
                                428      028C 428
                                429      028C 429
                                430      028C 430
                                .END
```



```

ACMASK      = 0000407C
APPROX      = 00000205 R      02
EVAL        = 000001FB R      02
EXCEPT    = 00000276 R      02
GXPLN      = 00000009
GXPLN1     = 00000009
GXPTAB      = 00000148 R      02
GXPTB1      = 00000100 R      02
G_16LOG2_E  = 00000190 R      02
G_LN2_OV_16_HI = 00000198 R      02
G_LN2_OV_16_LO = 000001A0 R      02
LONG        = 00000004
MTH$$JACKET_HND ***** X      02
MTH$$JACKET_TST ***** X      00
MTH$$SIGNAL ***** X      00
MTH$GEXP    = 000001A8 RG      02
MTH$GEXP_R6 = 000001B9 RG      02
MTH$GEXP_R7 = 000001B9 RG      02
MTH$K_FLOOVEMAT ***** X      00
MTH$K_FLOUNDMAT ***** X      00
OVER        = 0000027A R      02
SFSW_SAVE_PSW = 00000004
SMTST       = 00000237 R      02
TABHI       = 00000000 R      02
TABLO       = 00000080 R      02
UNDER       = 00000252 R      02
X           = 00000004
X_16LOG2E   = 00001760

```

```

+-----+
! Psect synopsis !
+-----+

```

PSECT name	Allocation	PSECT No.	Attributes										
. ABS .	00000000 (0.)	00 (0.)	NOPIC USR	CON	ABS	LCL	NOSHR	NOEXE	NORD	NOWRT	NOVEC	BYTE	
\$AB\$\$	00000000 (0.)	01 (1.)	NOPIC USR	CON	ABS	LCL	NOSHR	EXE	RD	WRT	NOVEC	BYTE	
_MTH\$CODE	0000028C (652.)	02 (2.)	PIC USR	CON	REL	LCL	SHR	EXE	RD	NOWRT	NOVEC	LONG	

```

+-----+
! Performance indicators !
+-----+

```

Phase	Page faults	CPU Time	Elapsed Time
-----	-----	-----	-----
Initialization	31	00:00:00.11	00:00:00.88
Command processing	104	00:00:00.64	00:00:04.12
Pass 1	129	00:00:01.95	00:00:06.65
Symbol table sort	0	00:00:00.03	00:00:00.04
Pass 2	92	00:00:01.15	00:00:02.39
Symbol table output	4	00:00:00.04	00:00:00.09
Psect synopsis output	2	00:00:00.01	00:00:00.02
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	364	00:00:03.95	00:00:14.22

The working set limit was 900 pages.
8602 bytes (17 pages) of virtual memory were used to buffer the intermediate code.

MTH\$GEXP
VAX-11 Macro Run Statistics

; G Floating Exponential Function

G 12

16-SEP-1984 01:27:00
6-SEP-1984 11:23:37

VAX/VMS Macro V04-00
[MTHRTL.SRC]MTHGEXP.MAR;1

Page 12
(5)

There were 10 pages of symbol table space allocated to hold 56 non-local and 5 local symbols.
490 source lines were read in Pass 1, producing 13 object records in Pass 2.
9 pages of virtual memory were used to define 8 macros.

+-----+
! Macro library statistics !
+-----+

Macro library name

Macros defined

_S255\$DUA28:[SYSLIB]STARLET.MLB;2

4

88 GETS were required to define 4 macros.

There were no errors, warnings or information messages.

MACRO/ENABLE=SUPPRESSION/DISABLE=(GLOBAL,TRACEBACK)/LIS=LIS\$:MTHGEXP/OBJ=OBJ\$:MTHGEXP MSRC\$:MTHJACKET/UPDATE=(ENHS:MTHJACKET)+MSRC\$:

0260 AH-BT13A-SE
VAX/VMS V4.0

DIGITAL EQUIPMENT CORPORATION
CONFIDENTIAL AND PROPRIETARY

